



PatSim 200

A cost effective, easy to use Patient Simulator



The PatSim 200 from Rigel was designed to make every patient simulation quicker.

Unlike other Patient Simulators, the PatSim uses a home and recall function to easily move between tests and store your most used sequences, no more clicking and scrolling through 'tree style' hierarchy to perform each test.

Why buy the PatSim 200?

- > The PatSim 200 saves and recall 5 of your most used simulations at the touch of just 3 buttons
- > An instant low-cost replacement for old patient simulators - the PatSim 200 is compatible with legacy IBP and temperature cables.
- > Rechargeable Li-Ion battery offering 8 hours of operation between charging

Key Features:

- > Simple, fast navigation
- > High contrast and low luminance colour display
- > Recall most used simulations
- > Foetal / maternal monitoring
- > Over 40 selectable arrhythmias

Passionate about patient safety.
T: +44 (0) 191 587 8730 E: sales@rigelmedical.com



RIGEL MEDICAL
TESTED, TRUSTED... WORLDWIDE.

See the **PatSim 200** for yourself, request your **FREE** live online demonstration today at rigelmedical.com/patsim200



What's in the box?

- > Quick start guide
- > Universal USB power supply
- > 10 x applied part adaptors
- > Calibration certificate
- > PatSim 200 Simulator
- > PatSim 200 carry case

Optional Accessories:

- > Replacement battery (404A954)
- > Temperature cable - unterminated (404A955)
- > IBP cable - unterminated (404A956)
- > Replacement carry case (404A950)
- > Applied part adaptors (404A951)
- > Universal USB power supply (404A952)

Technical Specification:

General ECG

Simulation	Full 12 lead ECG with independent outputs for each signal lead
Lead I	70%
Lead II	100%
Lead III	30%
Lead V1	24%
Lead V2	48%
Lead V3	100%
Lead V4	120%
Lead V5	112%
Lead V6	80%

ECG Normal Sinus Rhythm

Simulation	Full 12 lead ECG with independent outputs for each signal lead
Heart Rate	18 selectable values 30-300 bpm
Accuracy	±1BPM or 1%
Amplitude (lead II)	0.05 mV to 0.45 mV (0.05 mV steps)
	0.5 mV to 5.5 mV (0.5 mV steps)
Amplitude Accuracy	± 2%
ST Segments	18 selectable values, 8 elevated & 8 depressed
Neonatal Mode	ECG R wave width is reduced to 40ms

Arrhythmia Waveforms (Atrial)

Amplitude (lead II)	0.05 mV to 0.45 mV (0.05 mV steps)
	0.5 mV to 5.5 mV (0.5 mV steps)
Amplitude Accuracy	± 2%
Ventricular Waveforms	Asystole
	Bigeminy
	Trigeminy
	Ventricular Fibrillation (coarse)
	Ventricular Fibrillation (fine)
	Ventricular Tachycardia
Supraventricular Waveforms	Atrial Fibrillation coarse
	Atrial Fibrillation fine
	Atrial Flutter
	Atrial Tachycardia
	Missing beat
	Nodal rhythm
	Paroxysmal Atrial Tachycardia
	Sinus Arrhythmia
	Supraventricular Tachycardia

Passionate about patient safety.

T: +44 (0) 191 587 8730 E: sales@rigelmedical.com



RIGEL MEDICAL
TESTED, TRUSTED... WORLDWIDE.

See the **PatSim 200** for yourself, request your **FREE** live online demonstration today at **rigelmedical.com/patsim200**



Service and Warranty

The PatSim 200 comes with a free upgraded 5-year warranty, subject to terms and conditions, available at

rigelmedical.com/register

Technical Specification (Continued):

Arrhythmia Waveforms (Atrial) (Continued)

Atrial Conduction Waveforms	First Degree AV Block Left Bundle Branch Block Right Bundle Branch Block Second Degree AV Block - Mobitz I Second Degree AV Block - Mobitz II Third Degree AV Block
Premature Waveforms	Premature Atrial Contraction Premature Nodal Contraction Premature Left Ventricle Contraction Premature Left Ventricle Contraction - early Premature Right Ventricle Contraction - R on T Premature Ventricular Contraction - 6 / min Premature Ventricular Contraction - 12 / min Premature Ventricular Contraction - 24 / min Premature Ventricular Contraction - frequent multifocal

Performance Waveforms

Square Waves	2 Hz, 0.125 Hz
Triangle Wave	2 Hz
Pulse	60bpm or 240bpm
Sine Waves	0.05, 0.5, 1, 10, 25, 30, 40, 50, 60, and 100 Hz
R-Wave Detector Test	60 BPM haver-triangle wave with selectable width and amplitude
Haver-triangle Width	12 selectable values between 8 and 200 ms
Performance amplitude	0.5 to 5.0 mV in 0.5 mV steps

Pacer Waveforms

Simulated Rhythms	Asynchronous at 75 bpm Demand with frequent sinus beat Demand with occasional sinus beat A-V sequential Non-capture Non-function
Pulse Amplitude	1.0, 2.0, 5.0, 10.0 mV
Accuracy	±10%
Width	5 selectable values 0.1-2.0 ms
Accuracy	± 5%

Passionate about patient safety.

T: +44 (0) 191 587 8730 E: sales@rigelmedical.com



RIGEL MEDICAL
TESTED, TRUSTED... WORLDWIDE.

See the **PatSim 200** for yourself, request your **FREE** live online demonstration today at rigelmedical.com/patsim200



Technical Specification (Continued):

R Wave Detection

Heart Rate	6 selectable values 30-250 BPM
Amplitude	0.05 mV to 0.50 mV (0.05 mV steps)
R wave width	13 selectable values 8-200ms

Respiration Simulation

Rates	0, 5, 10, 15, 30, 40, 60, 80, 120, 180 brpm
Resistance Variations	0.2, 0.5, 1.0, 3.0 Ω
Accuracy	±10%
Base resistances	500, 1000, 1500 and 2000 Ω
Accuracy	±5%
Lead selection	1 (LA), 2(LL) user selectable
Apnoea Simulation	Manual on/off

Temperature Simulation

Simulation	YSI 400 / 700A / 700B Static
Temperature unit	°C or °F, user selectable
Range	pre-set 4 values at 0.0, 24.0, 37.0, and 40.0°C pre-set 4 values at 32.0, 75.2, 98.6, 104.0°F
Accuracy	± 0.1 °C / °F
Connector	mini-DIN style

Invasive Blood Pressure Simulation

Channels	2 channels
Static Pressure	-10, 5,0,20,40,50,60,80,100,150,160, 200,240,320, 400mmHg
Dynamic Simulation	Arterial [ART] 120/80 Radial Artery [RA] 120/80 Left Ventricle [LV] 120/00 Right Ventricle [RV] 25/00 Right Atrium (central venous) [CVP] 15/10 Pulmonary Artery [PA] 25/10 Pulmonary Artery Wedge [PAW] 10/2 Left Atrium [LA] 14/4

Invasive Blood Pressure Simulation (Continued)

Auto sequence (C1 only)	Cycle through simulations with 15 second step duration: Arterial [ART] 120/80 Radial Artery [RA] 120/80 Left Ventricle [LV] 120/00 Right Ventricle [RV] 25/00 Pulmonary Artery Wedge [PAW] 10/2
-------------------------	--

Passionate about patient safety.
T: +44 (0) 191 587 8730 E: sales@rigelmedical.com



RIGEL MEDICAL
TESTED, TRUSTED... WORLDWIDE.

See the **PatSim 200** for yourself, request your FREE live online demonstration today at rigelmedical.com/patsim200



Technical Specification (Continued):

Invasive Blood Pressure Simulation (Continued)

	[PAW] 10/2 Pulmonary Artery [PA] 25/10 Right Atrium (central venous) [CVP] 15/10
Accuracy	± 1mmHg
Excitation voltage	2V to 16V
Impedance	350Ω Nominal
Simulated sensitivity	5µV/V/mmHg or 40µV/V/mmHg (user selectable)
Connector	mini-DIN style

General Specification:

Mains power/Battery info	3.7V 3900mAh 14.4WH Li-Ion battery 5V 1A USB micro-B power supply 100-240V ~ 50/60Hz 0.18A max.
Charge time (new battery)	Up to 6 hours
Battery life	Up to 8 hours (depending on simulation and screen brightness)
Weight	0.70 Kg / 1.5 lbs
Dimensions	180 x 150 x 55 mm, 7.1 x 5.9 x 2.2 inch

Serviceability

Warranty:	5 years [terms and conditions apply]
Calibration:	1 year

Environmental

Operating conditions	10 - 40°C (50 - 104°F) 0-90% RH - NC
Storage environment	-15 - 60°C (5 - 140°F) 0-90% RH - NC
Environmental protection	IP40
Impact Rating	IK08

Electrical Interfaces

ECG (& respiration)	10 x 4 mm sockets
BP 1 - 2	6 pin mini DIN
Temperature	8 pin mini-DIN
USB Port	micro

Rev 3

Passionate about patient safety.

T: +44 (0) 191 587 8730 E: sales@rigelmedical.com



RIGEL MEDICAL
TESTED, TRUSTED... WORLDWIDE.

See the **PatSim 200** for yourself, request your FREE live online demonstration today at **rigelmedical.com/patsim200**